

ACCESSORIES

SILENCER AND VISUAL INDICATOR

■ BESL Throttle Silencer

	Model	BESL-01	BESL-02	BESL-03	BESL-04	BESL-06
	Thread(PT)	1/8	1/4	3/8	1/2	3/4

■ BSL Brass Silencer

	Model	BSL-M5	BSL-01	BSL-02	BSL-03	BSL-04	BSL-06
	Thread(PT)	M5	1/8	1/4	3/8	1/2	3/4

■ BSLM Brass Silencer Flat

	Model	BSLM-01	BSLM -02	BSLM -03	BSLM -04	BSLM -06
	Thread(PT)	1/8	1/4	3/8	1/2	3/4


■ PAL Plastic Silencer(Porous Polyethene)

	Model	PAL-01	PAL -02	PAL -03	PAL -04	PAL -06
	Thread(PT)	1/8	1/4	3/8	1/2	3/4

■ PSL Plastic Silencer(Sintered)

	Model	PSL-01	PSL-02	PSL-03	PSL-04	PSL-06
	Thread(PT)	1/8	1/4	3/8	1/2	3/4

■ APP Plug

	Model	APP4	APP6	APP8	APP10	APP12	APP16
	Tube ϕ D(mm)	ϕ 4	ϕ 6	ϕ 8	ϕ 10	ϕ 12	ϕ 16

■ VISUAL INDICATOR Ordering code

<u>VIS</u>	<u>001</u>	<u>04</u>	<u>A</u>
Model	Port size	Unactuated-Actuated colour	
VSI: Visual indicator	04: M5 $\times$ 0.8 06: 1/8"	A: red -green B: green -red C: blue -red D: red -blue E: black -red F: red -black	

Specification

	Type	VIS-001-04	VIS001-06
	Media	Compressed air	
	Port size code	04	06
	Port size	M5 $\times$ 0.8	1/8"
	Operating pressure	Full actuation	0.5~7bar(0.05~0.7Mpa)(7~100Psi)
		Full de-actuation	0~0.15bar(0~0.015Mpa)(0~2Psi)
	Mounting	Panel	

Remarks: Mounting panel-hole ϕ 31mm, thickness less than 9mm.